MIAMI-DADE COUNTY, FLORIDA METRO-DADE FLAGLER BUILDING

140 WEST FLAGLER STREET, SUITE 1603 MIAMI, FLORIDA 33130-1563 (305) 375-2901 FAX (305) 375-2908

www.miamidade.gov

#### **NOTICE OF ACCEPTANCE (NOA)**

Eastern Metal Supply, Inc. 3600 23<sup>rd</sup> Avenue South Lake Worth, Florida 33461

#### SCOPE:

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed by Miami-Dade County Product Control Division and accepted by the Board of Rules and Appeals (BORA) to be used in Miami Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Division (In Miami Dade County) and/or the AHJ (in areas other than Miami Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. BORA reserves the right to revoke this acceptance, if it is determined by Miami-Dade County Product Control Division that this product or material fails to meet the requirements of the applicable building code.

This product is approved as described herein, and has been designed to comply with the High Velocity Hurricane Zone of the Florida Building Code.

### DESCRIPTION: "Bertha HV" Aluminum Accordion Shutter System

**APPROVAL DOCUMENT:** Drawing No. 07-103, titled "Bertha HV Accordion Shutter System", sheets 1 through 10 of 10, prepared by Tilteco, Inc., dated April 24, 2007, last revision #1 dated July 09, 2007, signed and sealed by Walter A. Tillit Jr., P.E. bearing the Miami-Dade County Product Control Approval stamp with the Notice of Acceptance number and Approval date by the Miami-Dade County Product Control Division.

## MISSILE IMPACT RATING: Large and Small Missile Impact

**LABELING:** Each unit shall bear a permanent label with the manufacturer's name or logo, city, state and the following statement: "Miami-Dade County Product Control Approved", unless otherwise noted herein.

**RENEWAL** of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

**TERMINATION** of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

**ADVERTISEMENT:** The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

**INSPECTION:** A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official.

This NOA consists of this page 1, evidence submitted pages E-1, E-2, & E-3 as well as approval document mentioned above.

The submitted documentation was reviewed by Helmy A. Makar, P.E., M.S.



Heling A. Melon 08/02/2007

NOA No. 07-0509.14 Expiration Date: 08/02/2012 Approval Date: 08/02/2007

Page 1

#### Eastern Metal Supply, Inc.

#### NOTICE OF ACCEPTANCE: EVIDENCE SUBMITTED

### 1. EVIDENCE SUBMITTED UNDER PREVIOUS APPROVAL #03-0542

#### A. DRAWINGS:

1. Drawing No. 03-033, titled "Bertha High Velocity Accordion Shutter System", sheets 1 through 12 of 12, prepared by Tilteco, Inc., dated May 20, 2003, last revision #1 dated October 6, 2003, signed and sealed by Walter A. Tillit Jr., P.E.

#### B. TESTS:

1. Test report on Large Missile Impact Test, Cyclic Wind Pressure Test, and Uniform Static Air Pressure Test of Accordion Shutter, prepared by American Test Lab of South Florida, Report No. ATL SF #0214.01-03, dated 07/18/03, signed and sealed by William R. Mehner, P.E and Henry Hattem, P.E.

#### C. CALCULATIONS:

- 1. Comparative Analysis and Anchor calculation, dated June 17, 2003, sheets 1 through 194, prepared by Tilteco, Inc., signed and sealed by Walter A. Tillit Jr., P.E.
- 2. Anchor analysis dated October 06, 2003, one sheet, prepared by Tilteco, Inc., signed and sealed by Walter A. Tillit Jr., P.E.

#### D. QUALITY CONTROL

1. By Miami-Dade County Building Code Compliance Office.

#### E. MATERIAL CERTIFICATION:

- 1. Mill Certified Test Report issued by Indalex with chemical composition and mechanical properties for aluminum alloy 6063-T6.
- 2. Tensile Test Report No. 3DM-388,two sheets, prepared by QC Metallurgical, Inc., dated May 20, 2003, signed and sealed by Frank E. Grate Jr., P.E.

## 2. EVIDENCE SUBMITTED UNDER PREVIOUS APPROVAL # 04-0052

#### A. DRAWINGS:

1. Drawing No. 03-033, titled "Bertha High Velocity Accordion Shutter System", sheets 1 through 14 of 14, prepared by Tilteco, Inc., dated May 20, 2003, last revision #3 dated January 21, 2004, signed and sealed by Walter A. Tillit Jr., P.E.

#### B. TESTS:

1. Test report on Large Missile Impact Test, Cyclic Wind Pressure Test, and Uniform Static Air Pressure Test of Accordion Shutter, prepared by American Test Lab of South Florida, Report No. ATL SF #0214.01-03, dated 07/18/03, signed and sealed by William R. Mehner, P.E and Henry Hattem, P.E.

Helmy A. Makar, P.E., M.S. Product Control Examiner NOA No. 07-0509.14

He Curs

**Expiration Date: 08/02/2012 Approval Date: 08/02/2007** 

#### Eastern Metal Supply, Inc.

#### NOTICE OF ACCEPTANCE: EVIDENCE SUBMITTED

2. Test report on Large Missile Impact Test and Cyclic Wind Pressure Test of Accordion Shutter, prepared by American Test Lab of South Florida, Report No. ATL SF #0715.01-03, dated 01/21/04, signed and sealed by William R. Mehner, P.E and Henry Hattem, P.E.

#### C. CALCULATIONS:

1. Anchor calculation, dated November 3, 2003, sheets 1 through 43 of 43, prepared by Tilteco, Inc., signed and sealed by Walter A. Tillit Jr., P.E.

#### D. QUALITY CONTROL

1. By Miami-Dade County Building Code Compliance Office.

#### E. MATERIAL CERTIFICATION:

1. None.

### 3. EVIDENCE SUBMITTED UNDER PREVIOUS APPROVAL #05-0227

#### A. DRAWINGS:

1. Drawing No. 05-072, titled "Bertha HV Accordion Shutter System", sheets 1 through 14 of 14, prepared by Tilteco, Inc., dated May 19, 2005, last revision #2 dated July 12, 2005, signed and sealed by Walter A. Tillit Jr., P.E.

#### B. TESTS:

1. None.

#### C. CALCULATIONS:

1. None.

#### D. QUALITY CONTROL

1. By Miami-Dade County Building Code Compliance Office.

#### E. MATERIAL CERTIFICATION:

1. None.

#### F. OTHERS

1. Letter from Tilteco, Inc., dated July 12, 2005, signed and sealed by Walter A. Tillit Jr., P.E., certifying that drawing #05-072 is in compliance with the 2004 Edition of the Florida Building Code. Also, states that drawings 05-072 revises drawings 03-033 which is certified for code compliance in accordance with the 2001 Edition of the Florida Building Code.

Kelmy A. Makar, P.E., M.S. Product Control Examiner NOA No. 07-0509.14

**Expiration Date: 08/02/2012 Approval Date: 08/02/2007** 

#### Eastern Metal Supply, Inc.

## **NOTICE OF ACCEPTANCE: EVIDENCE SUBMITTED**

#### 4. NEW EVIDENCE SUBMITTED

#### A. DRAWINGS:

1. Drawing No. 05-363, titled "Bertha HV Accordion Shutter System", sheets 1 through 26 of 26, prepared by Tilteco, Inc., dated January 17, 2006, last revision #2 dated October 06, 2006, signed and sealed by Walter A. Tillit Jr., P.E.

#### B. TESTS:

- 1. Test report on Large Missile Impact Test, Cyclic Wind Pressure Test, and Uniform Static Air Pressure Test of Accordion Shutter, prepared by American Test Lab of South Florida, Report No. ATL SF #0422.01-05, dated 09/16/05, signed and sealed by William R. Mehner, P.E and Henry Hattem, P.E.
- 2. Test report on Large Missile Impact Test, Cyclic Wind Pressure Test of Accordion Shutter, prepared by American Test Lab of South Florida, Report # ATL SF #1004.01-05, dated 11/16/05, signed & sealed by William R. Mehner, P.E & Henry Hattem, P.E.
- 3. Test report on Large Missile Impact Test, Cyclic Wind Pressure Test of Accordion Shutter, prepared by American Test Lab of South Florida, Report No. ATL SF #1214.01-05, dated 12/19/05, signed and sealed by William R. Mehner, P.E and Henry Hattem, P.E.
- 4. Test report on Large Missile Impact Test, Cyclic Wind Pressure Test of Accordion Shutter, prepared by American Test Lab of South Florida, Report No. ATL SF #0317.02-06, dated 05/23/05, signed and sealed by William R. Mehner, P.E and Henry Hattem, P.E.

#### C. CALCULATIONS:

1. Comparative Analysis and Anchor calculation, dated September 08, 2006, sheets 1 through 298, prepared by Tilteco, Inc., signed and sealed by Walter A. Tillit Jr., P.E.

#### D. QUALITY CONTROL

1. By Miami-Dade County Building Code Compliance Office.

#### E. MATERIAL CERTIFICATION

- 1. Mill Certified Test Report issued by Indalex with chemical composition and mechanical properties for aluminum alloy 6005-T5.
- 2. Tensile Test Report No. 5JM-1022, 3 samples of 1004.01-05 Specimens A, B, C, prepared by QC Metallurgical, Inc., dated November 16, 2006, signed and sealed by Frank E. Grate Jr., P.E.
- 3. Tensile Test Report No. 5FM-578, 3 samples of 0422.01-05 Specimens A, B, C, prepared by QC Metallurgical, Inc., dated July 06, 2005, signed and sealed by Frank E. Grate Jr., P.E.

#### F. NOTES

1. This approval is selected details from Approval #05-0227.

Helmy A. Makar, P.E., M.S. Product Control Examiner

NOA No. 07-0509.14 Expiration Date: 08/02/2012

**Approval Date: 08/02/2007** 

#### **GENERAL NOTES:**

BERTHA H.V. ACCORDION SHUTTER SYSTEM SHOWN ON THIS PRODUCT APPROVAL DOCUMENT (P.A.D.) HAS BEEN VERIFIED FOR COMPLIANCE IN ACCORDANCE WITH THE 2004 EDITION OF THE FLORIDA BUILDING CODE WITH THE 2005 AND 2006 SUPPLEMENTS.

THIS ACCORDION SHUTTER SYSTEM MAY BE INSTALLED AT HIGH VELOCITY HURRICANE ZONES, DESIGN WIND LOADS SHALL BE DETERMINED AS PER SECTION 1620 OF THE ABOVE MENTIONED CODE. IN ORDER TO VERIFY THAT ANCHORS ON THIS P.A.D., AS TESTED, WERE NOT OVERSTRESSED, A 33 % INCREASE IN ALLOWABLE LOADS FOR WIND LOADS WAS NOT USED IN THEIR ANALYSIS, BERTHA H.V. ACCORDION SHUTTER SYSTEM'S ADEQUACY FOR WIND AND LARGE MISSILE IMPACT LOAD HAS BEEN VERIFIED IN ACCORDANCE WITH SECTION 1609.1.4 OF THE ABOVE MENTIONED CODE AS PER ATL REPORTS:

- -HV BLADE 1 #0214.01-03, #0715.01-03, #1004.01-05, #1214.01-05 AND 0317.02-06 AS PER HIGH VELOCITY HURRICANE ZONE TAS-201, TAS-202 AND TAS-203 PROTOCOLS
- 2. BERTHA H.V. ACCORDION PINS (HV SCREWS), USED AT BLADES KNUCKLE AND FOR DIRECT MOUNT CONNECTION TO TRACKS SHALL BE # 14X2.75 AND # 14X1.75 RESPECTIVELY, 410-HT MINIMUM SERIES STAINLESS STEEL SCREWS WITH 135.0 ksi YIELD STRENGTH AND 180 ksi TENSILE STRENGTH. PINS SHALL BE COATED WITH BERTHA HV DACROSHIELD COATING SYSTEM AS MANUFACTURED BY APPROVED COATING APPLICATORS, REGISTERED WITH AMERICAN SHUTTER SYSTEMS ASSOCIATION. PINS MUST BEAR THE HV MARKING ON THEIR HEAD.
- 3. ALL ALUMINUM EXTRUSIONS SHALL BE ALUMINUM ASSOCIATION ALLOY AND TEMPER AS INDICATED ON SHEET 2. MINIMUM YIELD STRENGTH FOR 6063-T6 ALLOY IS 30.0 ksi.
- 4. ALL SCREWS TO BE STAINLESS STEEL 304 OR 316 AISI SERIES OR CORROSION RESISTANT COATED CARBON STEEL AS PER DIN 50018 WITH 50 ksi MIN. YIELD STRENGTH AND 90 ksi MIN. TENSILE STRENGTH.
- 5. BOLTS TO BE ASTM A-307 GALVANIZED STEEL, OR AISI 304 OR 316 SERIES STAINLESS STEEL WITH 35 ksi MINIMUM YIELD STRENGTH.
- 6. SEE THE FOLLOWING SHEETS FOR ANCHOR SPECIFICATIONS: HV BLADE ① : 7, 8 AND 9.
- 7. THIS BERTHA H.V. ACCORDION SHUTTER SYSTEM BEARS A U.S. PATENT #6'779,582. COMPONENTS OF THIS APPROVAL ARE COVERED, IN WHOLE OR IN PART BY U.S. PATENT #5'458,179 ISSUED TO EASTERN METAL SUPPLY, INC.
- 8. IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO VERIFY THE SOUNDNESS OF THE STRUCTURE WHERE SHUTTER IS TO BE ATTACHED TO INSURE PROPER ANCHORAGE. CONTRACTOR TO SEAL/CAULK ALL SHUTTER COMPONENT EDGES WHICH REMAIN, THRU FASTENING IN CONTINUOUS CONTACT WITH THE BUILDING TO PREVENT WIND/RAIN INTRUSION.
- 9. EACH UNIT MUST BEAR PERMANENT LABEL IN A VISIBLE PLACE WITH WARNING NOTE: DURING PERIODS OF HURRICANE WARNINGS HOME OWNER, TENANT, OR OTHERS, MUST PROPERLY CLOSE ALL HV CENTERMATES AND ENGAGE OR LOCK ALL HV LOCKS.
- 10. SHUTTER'S MANUFACTURER LABEL SHALL BE PLACED ON A READILY VISIBLE LOCATION. ONE LABEL SHALL BE PLACED FOR EVERY OPENING, LABEL SHALL READ AS FOLLOWS: EASTERN METAL SUPPLY, INC. LAKEWORTH, FL.

MIAMI-DADE COUNTY PRODUCT CONTROL APPROVED.

- 11. BERTHA H.V. ACCORDION SHUTTER SYSTEM'S INSTALLATION SHALL COMPLY WITH SPECS INDICATED IN THIS DRAWING PLUS ANY BUILDING AND ZONING REGULATIONS PROVIDED BY THE JURISDICTION WHERE PERMIT IS APPLIED TO.
- 12. (a) THIS P.A.D. PREPARED BY THIS ENGINEER IS GENERIC AND DOES NOT PROVIDE INFORMATION FOR A SITE SPECIFIC PROJECT; i.e. WHERE THE SITE CONDITIONS DEVIATE FROM THE
- (b) CONTRACTOR TO BE RESPONSIBLE FOR THE SELECTION, PURCHASE AND INSTALLATION INCLUDING LIFE SAFETY OF THIS PRODUCT, BASED ON THIS P.A.D., PROVIDED HE/SHE DOES NOT DEVIATE FROM THE CONDITIONS DETAILED ON THIS DOCUMENT. CONSTRUCTION SAFETY AT SITE IS THE CONTRACTOR'S RESPONSIBILITY.
- (c) THIS P.A.D. WILL BE CONSIDERED INVALID IF ALTERED BY ANY MEANS.
- (d) SITE SPECIFIC PROJECTS SHALL BE PREPARED BY A FLORIDA REGISTERED ENGINEER OR ARCHITECT WHICH WILL BECOME THE ENGINEER OF RECORD (E.O.R.) FOR THE PROJECT AND WHO WILL BE RESPONSIBLE FOR THE PROPER USE OF THE P.A.D. ENGINEER OF RECORD, ACTING AS A DELEGATED ENGINEER TO THE P.A.D. ENGINEER SHALL SUBMIT TO THIS LATTER THE SITE SPECIFIC DRAWINGS FOR REVIEW.
- (e) THIS P.A.D. SHALL BEAR THE DATE AND ORIGINAL SEAL AND SIGNATURE OF THE PROFESSIONAL ENGINEER OF RECORD THAT PREPARED IT.

Approved as complying with the

Florida Building Code
Date 08/02/2007

NOA# 07-0509.14

Miarai Bade Product Control

### TABLE OF CONTENTS

#### AREA 1: GENERAL NOTES AND SPECS

GENERAL NOTES	SHEET 1
SYSTEM COMPONENTS	SHEET 2
TYPICAL SHUTTER ASSEMBLY	SHEET 3

#### AREA 2: HV BLADE 1 DETAILS

TYPICAL SHUTTER ELEVATION & NOTES ON LOCKS. INSTALLATION DETAILS CONCRETE/BLOCK CENTERMATE AND	SHEET 4 SHEET 5
END CONNECTION DETAILS CONCRETE/BLOCK MAXIMUM SPAN TABLES AND	SHEET 6
ANCHOR SPECS - CONCRETE & BLOCK ANCHOR SCHEDULE- CONCRETE & BLOCK ANCHOR SCHEDULE- WOOD INSTALLATION AND	SHEET 7 SHEET 8 SHEET 9
END CONNECTION DETAILS - WOOD	SHEET 10

F.B.C.(High Velocity Hurricane Zone)

© 2003 EASTERN METAL SUPPLY, INC.

**BERTHA HV™ Accordion Shutter System** 

REV. No DESCRIPTION DATE Drawn by: F.P. GENERAL 07/09/07 DATE: 04/24/07 1 2 DRAWING No. 3 07-103 4 5 SHEET OF 10

ILLECO

TILLIT TESTING & ENGINEERING COMPANY 355 N.W. 36th. St., Ste. 305, VIRGINIA GARDENS, FLORIDA 33166

EASTERN METAL SUPPLY, INC.

(ASSA # 1)

3600 23 AVE. SOUTH

LAKEWORTH, FL 33461

PH: (561)533-6061 FAX: (561)588-4780


Phone : (305)871-1530 . Fax : (305)871-1531 e-mail: tilteco@aal.com EB-0006719

P.E. SEAL/SIGNATURE/DATE


down to

JUL 1 0 2007

WALTER A. TILLIT Jr. P. E. FLORIDA Lic. # 44167





1 HY BLADE COVERED UNDER US PATENT # 5458179 6063-T6 ALLOY AND TEMPER




















**HV EGRESS LOCK** 

Approved as complying with the Florida Building Code
Date 08/02/2007

JUL 1 0 2007

P.E. SEAL/SIGNATURE/DATE



TILLIT TESTING & ENGINEERING COMPANY 6355 N.W. 36th. St., Ste. 305, VIRGINIA GARDENS, FLORIDA 33166 Phone: (305)871-1530 . Fax: (305)871-1531
e-maii: tilteco@aol.com
E8-0006719
WALTER A. TILLIT Jr. P. E. FLORIDA Lic. # 44167

## EASTERN METAL SUPPLY, INC. (ASSA # 1)

3600 23 AVE. SOUTH LAKEWORTH, FL 33461 PH: (561)533-6061 FAX: (561)588-4780

© 2003 EASTERN METAL SUPPLY, INC. BERTHA HV™ **Accordion Shutter System** 

F.B.C.(High Velocity Hurricane Zone)


			- J
REV. No	DESCRIPTION	DATE	Drawn by: F.P.
1	GENERAL	07/09/07	DATE: 04/24/07
2			DRAWING No
3			07-103
4			0/-103
5			SHEET
6			2 OF 10

## SHUTTER ASSEMBLY SCHEDULE FOR HV 1 HV BLADE 1 38 HV LONG RECESSED NYLON BUSHING 39 HV SHORT RECESSED NYLON BUSHING 40 HV NYLON HAT WASHER (41) HV WHEEL CARRIAGE AISI 302-303 SERIES ø.870"x3/16" THICK NYLON WHEEL. 0.188" AISI 302 SERIES S.S. RIVETS #14 x 1 3/4" ACCORDION PIN W/ #8 HEAD 43 #14 x 2 3/4" ACCORDION PIN W/ #8 HEAD


#### HV PIN REQUIREMENTS

(1) HV PIN (3) SHALL ALWAYS BE USED AT ALL (EXTERIOR AND INTERIOR, TOP AND BOTTOM) KNUCKLES.

(2) HV PIN (2) OR (3) W/ 1/2' O.D. 1/16' THICK S.S. WASHER SHALL BE USED FOR DIRECT MOUNT INSTALLATION (OF COMPONENT # 4) PER DETAIL X, SHEETS 6 AND 10.




#### **EXTERIOR**




## TYPICAL SHUTTER ASSEMBLY

SCALE: 3/8" = 1"



## WHEEL CARRIAGE DETAIL



F.B.C.(High Velocity Hurricane Zone)

© 2003 EASTERN METAL SUPPLY, INC.

## **BERTHA HV™**

**Accordion Shutter System** 

			•
REV. No	DESCRIPTION	DATE	Drawn by: F.P.
1	GENERAL	07/09/07	DATE: 04/24/07
2			DRAWING No
3			07-103
4			0/-103
5			SHEET
6			3 OF 10

Approved as complying with the Florida Buiding Code
Date 08/02/2007 NOA# 07-0569.14 Miami Dade Product Control

JUL 1 0 2007

P.E. SEAL/SIGNATURE/DATE

## IL ECO INC.


TILLIT TESTING & ENGINEERING COMPANY 355 N.W. 36th. St., Ste. 305, VIRGINIA GARDENS, FLORIDA 33166 Phone: (305)871-1530 . Fax: (305)871-1531 e-mail: tilteco@aal.com EB-0006719 WALTER A. TILLIT Jr. P. E.

FLORIDA Lic. # 44167

3600 23 AVE. SOUTH LAKEWORTH, FL 33461 PH: (561)533-6061 FAX: (561)588-4780

EASTERN METAL SUPPLY, INC.

(ASSA # 1)



#### \* NOTES ON HV LOCKS AND CENTERMATES:

- 1. MANDATORY CONDITION #1: ONE HV LOCK 24 or 25 SHALL BE USED AT 1/2 OF SHUTTER SPAN FOR ANY SPAN OR 12" ABOVE OR BELOW 1/2 OF SHUTTER SPAN FOR SPANS UP TO 90", AND FOR INSTALLATIONS AT ANY ELEVATION. HV LOCK 24 or 25 MAY BE USED AS AN INSIDE OR OUTSIDE LOCK, ATTACHED TO 20 CENTERMATE W/(2) 1/4" Ø-20 x 1/2" LONG FLAT HEAD S.S. M.S. LOCATION OF LOCK SHALL BE AS INDICATED ON TYPICAL SHUTTER ELEVATION.
- 2. **OPTIONAL CONDITION \$1:** IF DESIRED, FOR BETTER PERFORMANCE OR FOR SECURITY PURPOSES, UP TO TWO HY LOCKS (2) OR (3) MAY BE USED AS AN INSIDE OR OUTSIDE LOCK. CONNECTION OF LOCKS TO CENTERMATES (2) SHALL BE AS INDICATED ON NOTE (1) ABOVE. LOCATION OF LOCKS SHALL BE AS INDICATED ON TYPICAL SHUTTER ELEVATION.

## TYPICAL SHUTTER ELEVATION

Approved as complying with the Florida Building Code
Date 08/02/2007
NOAW 07-0509.14
Minmi Dade Product Control
Division
By A. M.

JUL 1 0 2007

P.E. SEAL/SIGNATURE/DATE

# TILIECO INC.

TILLIT TESTING & ENGINEERING COMPANY
\$355 N.W. 36th. St., Ste. 305, VIRGINIA GARDENS, FLORIDA 33166
Phone: (305)871-1530 . Fox: (305)871-1531
e-mail: tilteco@aal.com
EB-0006719
WALTER A. TILLIT Jr. P. E.
FLORIDA Lic. # 44167


## EASTERN METAL SUPPLY, INC. (ASSA # 1)

3600 23 AVE. SOUTH LAKEWORTH, FL 33461 PH: (561)533-6061 FAX: (561)588-4780 F.B.C.(High Velocity Hurricane Zone)


© 2003 EASTERN METAL SUPPLY, INC.


# **BERTHA HV**<sup>™</sup> Accordion Shutter System

REV, No	DESCRIPTION	DATE	Drawn by: F.P.
1	GENERAL	07/09/07	DATE: 04/24/07
2			DRAWING No
3			
4			07-103
5			SHEET
6			4 OF 10




## (A) HV WALL HEADER INSTALLATION





1 HV WALK-OVER INSTALLATION




L HV WALL WALK-OVER INSTALLATION

NOTE FOR COMBINATION OF SECTIONS:

1- SEE SHEET 3 FOR TYPICAL SHUTTER
ASSEMBLY
2- MOUNTING SECTIONS CAN BE COMBINED
IN ANY WAY TO SUIT ANY INSTALLATION.

\* E. D. = EDGE DISTANCE (SEE SPECIFICATIONS ON SHEET 7)

## INSTALLATION DETAILS



JUL 1 0 2007

P.E. SEAL/SIGNATURE/DATE



TILLIT TESTING & ENGINEERING COMPANY
6355 N.W. 36th. St., Ste. 305, VIRGINIA GARDENS, FLORIDA 33166
Phone: (305)871-1530 . Fax: (305)871-1531
e-mail: tilteco@ool.com
EB-0006719
WALTER A. TILLIT Jr. P. E.
FLORIDA LIC. # 44167

## EASTERN METAL SUPPLY, INC. (ASSA # 1)

3600 23 AVE. SOUTH LAKEWORTH, FL 33461 PH: (561)533-6061 FAX: (561)588-4780 F.B.C.(High Velocity Hurricane Zone)
© 2003 EASTERN METAL SUPPLY, INC.


# **BERTHA HV™** Accordion Shutter System

REV. No DESCRIPTION DATE Drawn by: F.P.

1 GENERAL 07/09/07 DATE: 04/24/07

2 DRAWING No 07-103

5 SHEET 5 OF 10



#### SCHEDULE #1

	AXIMUM SHUTTER SPAN "L" (ft.)  FOR INSTALLATIONS W/  SYMMETRICAL CENTERMATES, (21)  I/ ONE HV LOCK (24) or (25)
MAXIMUM	CONCRETE & WOOD INSTALLATIONS A
DESIGN LOAD (p.s.f.) (+ OR -)	WALL MOUNTING OR WALL/FLOOR MOUNTING
	"L" (ft)
75	7'-6"

A MAXIMUM SHUTTER SPAN "L" FOR INSTALLATIONS INTO WOOD SHALL BE LIMITED TO 75 psf. DESIGN LOAD.

INSTALLATION LEGEND					
CONCRETE & MANSORY WOOD					
WALL MOUNTING	A & L.	М, Р & О.			
FLOOR MOUNTING	ļ	Х			

#### ♦ SEPARATION TO GLASS REQUIREMENTS

SEE BELOW FOR MINIMUM SEPARATION TO GLASS SCHEDULE FOR SHUTTERS INSTALLED WITHIN THE FIRST 30'-0" ELEVATION OF BUILDING MEASURED AT BOTTOM OF SHUTTER.

## MINIMUM SEPARATION TO GLASS SCHEDULE: SHUTTER W/ ONE LOCK

SHUTTER SPAN	INSTALLATION W/ <b>SYMMETRICAL</b> CENTERMATES
90" OR LESS	3 5/16"

#### MINIMUM SEPARATION TO GLASS SCHEDULE: SHUTTER W/ TWO LOCKS

SHUTTER SPAN	INSTALLATION W/ SYMMETRICAL CENTERMATES
90" OR LESS	2 3/4"

## \*SPECIFICATIONS ON ANCHOR REQUIREMENTS: POURED CONCRETE OR CONCRETE BLOCK SUBSTRATES

1. ANCHORS TO WALL SHALL BE AS FOLLOWS:

(A) TO EXISTING POURED CONCRETE: (Min. f'c = 3 ksi)

- 1/4" TAPCON ANCHORS, AS MANUFACTURED BY I.T.W. RAMSET/ RED HEAD.

#### NOTES:

- A.1) MINIMUM EMBEDMENT INTO POURED CONCRETE OF TAPCON ANCHORS IS 1 3/4".
- A.2) IN CASE THAT PRECAST STONE, PRECAST CONCRETE PANELS, PAVERS OR ANY VENEER BE FOUND ON THE EXISTING WALL OR FLOOR, ANCHORS SHALL BE LONG ENOUGH TO REACH THE MAIN STRUCTURE BEHIND SAID WALL FINISHES. ANCHORAGE SHALL BE AS INDICATED ON NOTE A.1) ABOVE. FOR INSTALLATIONS ON VINYL SIDING OR EIFS CONSULT THIS ENGINEER.
- (B) TO EXISTING CONCRETE BLOCK WALL: ASTM C-90.
- 1/4" TAPCON ANCHORS, AS MANUFACTURED BY I.T.W. RAMSET/ RED HEAD.

#### NOTES

- B.1) MINIMUM EMBEDMENT INTO CONCRETE BLOCK OF TAPCON ANCHORS, IS 1 1/4".
- B.2) IN CASE THAT PRECAST STONE, PRECAST CONCRETE PANELS, PAVERS OR ANY VENEER BE FOUND ON THE EXISTING WALL OR FLOOR, ANCHORS SHALL BE LONG ENOUGH TO REACH THE MAIN STRUCTURE BEHIND SAID WALL FINISHES. ANCHORAGE SHALL BE AS INDICATED ON NOTE B.1) ABOVE. FOR INSTALLATIONS ON VINYL SIDING OR EIFS CONSULT THIS ENGINEER.
- (C) ANCHORS SHALL BE INSTALLED FOLLOWING ALL OF THE RECOMMENDATIONS AND SPECIFICATIONS OF THE ANCHOR'S MANUFACTURER.
- (D) SEE SCHEDULE BELOW FOR EDGE DISTANCE (E.D.) VERSUS SPACING RELATIONSHIP FOR ANCHOR.

#### EDGE DISTANCE VERSUS SPACING FOR ANCHORS

MAXIMUM ANCHOR SPACINGS ARE VALID FOR 3 1/2" EDGE DISTANCE FOR 1/4" TAPCON FOR E. D. LESS THAN THE ABOVE MENTIONED, REDUCE ANCHOR SPACING BY MULTIPLYING SPACING SHOWN ON SCHEDULE BY THE FOLLOWING FACTORS. REDUCED SPACING OBTAINED USING FACTOR SHALL NOT BE LESS THAN MINIMUM SPACING INDICATED BELOW:

	FACTOR
ACTUAL E. D.	1/4"ø TAPCON
	MIN. SPACING = 3"
3"	0.83
2 1/2"	0.66
2"	0.50

Approved as complying with the Florida Building Code
Date 08/02/2007
NOA# 07-0509-11
Mismi Bade Product Control
Division

JUL 1 0 2007

P.E. SEAL/SIGNATURE/DATE



TILLIT TESTING & ENGINEERING COMPANY

5355 N.W. 36th. St., Ste. 305, VIRGINIA GARDENS, FLORIDA 33166

Phone: (305)871-1530 . Fax: (305)871-1531

e-mail: tilteco@aal.com

EB-0006719

EB-0006719
WALTER A. TILLIT Jr. P. E.
FLORIDA Lic. # 44167

# EASTERN METAL SUPPLY, INC. (ASSA # 1)

3600 23 AVE. SOUTH LAKEWORTH, FL 33461 PH: (561)533-6061 FAX: (561)588-4780 F.B.C.(**H**igh **V**elocity **H**urricane **Z**one)
© 2003 EASTERN METAL SUPPLY, INC.

# **BERTHA HV** ™ Accordion Shutter System

REV. No	DESCRIPTION	DATE	Drawn by: F.P.
1	GENERAL	07/09/07	DATE: 04/24/07
2			DRAWING No
3			07-103
4			0/-103
5			SHEET
6			7 OF 10

#### MAXIMUM DESIGN PRESSURE RATING (p.s.f.) AND CORRESPONDING MAXIMUM ANCHOR\* SPACING (in.) SCHEDULE FOR A GIVEN MAX. SHUTTER SPAN, DESIGN NEGATIVE LOAD AND A CORRESPONDING MOUNTING TYPE FOR CONCRETE OR CONCRETE BLOCK INSTALLATIONS

\* SEE ANCHOR **SPECIFICATIONS** ON SHEET 7

(SEE MOUNTINGS A, D, I AND L ON SHEET 5)

	P	OURED C	ONCRETE	Ξ	POURED (	CONCRETE	/CONCRE	TE BLOCK
(A) WALL HEADER MOUNTING MAXIMUM SPAN (ft)  (B) WALL HEADER MOUNTING W/(2).					3			
(,		DESIGN L	OAD (psf)			DESIGN L	OAD (psf)	
	30	40	60	75	30	40	60	75
3'-0" OR LESS	14	12	10	9	14	12	10	9
4'-0"	14	12	10	9	14	12	10	9
5'-0"	14	12	10	9	14	12	10	9
6'-0"	14	12	.10	9	14	12	10	8
7'-0"	14	12	10	9	14	12	9	5
7'-6"	14	12	10	8	14	11.5	7	3

MAXIMUM SPAN (ft)	Р	OURED C	ONCRETE		POURED CONCRETE/CONCRETE BLOCK									
	①WALK	OVER M AT FL		W/ ®	(L) WALL/WALK OVER MOUNTING W/(8)									
		DESIGN L	OAD (psf)		DESIGN LOAD (psf)									
	30	40	60	75	30	40	60	75						
3'-0" OR LESS	14	12	10	9	5	5	5	5						
4'-0"	14	12	10	9	5	5	5	5						
5'-0"	14	12	10	9	5	5	5	5						
6'-0"	14	12	10	9	5	5	5	5						
7'-0"	14	12	10	9	5	5	5	5						
7'-6"	14	12	10	8	5	5	5	5						

Approved as complying with the Florida Building Code 2007 Date 08/02/2007 NOAF 01-0509-14 Miami Dade Product Control

P.E. SEAL/SIGNATURE/DATE

JUL 1 0 2007

355 N.W. 36th. St., Ste. 305, VIRGINIA GARDENS, FLORIDA 33166 Phone : (305)871-1530 . Fax : (305)871-1531 e-mail: tilteco@aol.com EB-0006719

WALTER A. TILLIT Jr. P. E. FLORIDA Lic. # 44167

ILECO INC.

TILLIT TESTING & ENGINEERING COMPANY

# EASTERN METAL SUPPLY, INC.

3600 23 AVE. SOUTH LAKEWORTH, FL 33461 PH: (561)533-6061 FAX: (561)588-4780

(ASSA # 1)

© 2003 EASTERN METAL SUPPLY, INC. BERTHA HV TM **Accordion Shutter System** 

F.B.C.(High Velocity Hurricane Zone)

DESCRIPTION REV. No DATE Drawn by: F.P. 07/09/07 DATE: 04/24/07 GENERAL 2 DRAWING No 3 07-103 4 SHEET 5 8 OF 10

# MAXIMUM DESIGN PRESSURE RATING (p.s.f.) AND CORRESPONDING MAXIMUM ANCHOR SPACING (in.) SCHEDULE FOR A GIVEN MAX. SHUTTER SPAN, NEGATIVE DESIGN LOAD AND A CORRESPONDING MOUNTING TYPE.

(SEE MOUNTINGS ON SHEET 10).

	SUBSTRATE																											
MAXIMUM SPAN (ft)	SOUTHERN PINE No. 2 W/ MIN. G=0.55, DOUGLAS FIR W/ MIN. G=0.50						SPRUCE PINE FIR NORTH W/ MIN. G=0.43							SPRUCE PINE FIR SOUTH W/ MIN. G=0.36							1/2" MIN. CDX PLYWOOD							
	WALL MOUNTINGS M, O			FLOOR MOUNTINGS X			WAL	WALL MOUNTINGS M, O				FLOOR MOUNTINGS X				WALL MOUNTINGS M, O				FLOOR MOUNTINGS X				WALL MOUNTINGS P				
	NEGATIVE DESIGN LOAD (psf)			NEGAT	NEGATIVÉ DESIGN LOAD (psf)			NEGATIVE DESIGN LOAD (psf)			NEGATIVE DESIGN LOAD (paf)				NEGATIVE DESIGN LOAD (psf)			NEGATIVE DESIGN LOAD (psf)				NEGATIVE DESIGN LOAD (psf)						
	30	40	60	75	30	40	60	75	30	40	60	75	30	40	60	75	30	40	60	75	30	40	60	75	30	40	60	75
3'-0" OR LESS	12	10	10	9	6	6	6	6	12	10	10	9	6	6	6	6	12	10	10	9	6	6	6	6	6	5	4	4
4'-0"	12	10	10	9	6	6	6	6	12	10	10	9	6	6	6	6	12	10	10	9	6	6	6	6	6	5	4	4
5'-0"	12	10	10	9	6	6	6	6	12	10	10	9	6	6	6	6	12	10	10	9	6	6	6	6	6	5	4	4
6'-0"	12	10	10	9	6	6	6	6	12	10	10	9	6	6	6	5.5	12	10	10	9	6	6	6	6	6	5	4	4
7'-0"	12	10	10	9	6	6	6	5.5	12	10	10	9	6	6	6	5	12	10	10	7	6	6	6	5	6	5	4	4
7'-6"	12	10	10	7.5	6	6	6	5	12	10	10	6	6	6	5	4.5	12	10	10	4	6	6	5	4.5	6	5	4	-

#### + NOTES ON ANCHORS REQUIREMENTS: WOOD SUBSTRATES.

- 1. ANCHORS TO WALL, FLOOR OR SOLID WOOD SOFFIT SHALL BE AS FOLLOWS:
- 1/4" TAPCON ANCHORS, AS MANUFACTURED BY I.T.W. BUILDEX W/ MINIMUM EMBEDMENT AS INDICATED AT EACH SECTION ON SHEET 10. EXCEPTION: SEE NOTE 2 BELOW.
- 2. SUBSTRATE SHALL CONSIST OF THE FOLLOWING:
- -SOUTHERN PINE No. 2 W/ G=0.55 (N.D.S)
- -DOUGLAS FIR W/ G=0.50 (N.D.S.)
- -SPRUCE PINE FIR NORTH W/ G=0.43 (N.D.S.)
- -SPRUCE PINE FIR SOUTH W/ G=0.36 (N.D.S.)
- -MIN. 1/2" CDX PLYWOOD (1986 APA)
- 3. ANCHORS SHALL BE INSTALLED FOLLOWING ALL OF THE RECOMMENDATIONS AND SPECIFICATIONS OF THE ANCHOR'S MANUFACTURER.

ILLECO INC

TILLIT TESTING & ENGINEERING COMPANY 5355 N.W. 36th. St., Ste. 305, VIRGINIA GARDENS, FLORIDA 33166 Phone: (305)871-1530 . Fax: (305)871-1531 e-mail: tilteco@aol.com EB-0006719

WALTER A. TILLIT Jr. P. E. FLORIDA Lic. # 44167

## EASTERN METAL SUPPLY, INC. (ASSA # 1)


3600 23 AVE. SOUTH LAKEWORTH, FL 33461 PH: (561)533-6061 FAX: (561)588-4780 F.B.C.(High Velocity Hurricane Zone) © 2003 EASTERN METAL SUPPLY, INC.

**BERTHA HV** TM


Accordion Shutter System DESCRIPTION DATE Drawn by: F.P. 07/09/07 DATE: 04/24/07 GENERAL DRAWING No.

3 07 - 103SHEET 5 9 OF 10 6

Appreved as complying with the Florida Building Code / 2007 Date 08/02/2007 NOAS 07-0509-14



P.E. SEAL/SIGNATURE/DATE



EXISTING GLASS

MIN. SEPARATION TO GLASS

(SEE SCHEDULE

ON SHEET 7)

DRAWING No

07 - 103

10 OF 10

SHEET